# Panasonic ideas for life

Integrated Telephone System

## KX-TS580EX1/EX2 KX-TS560EX1/EX2 KX-TS520EX1/EX2

Caller ID Compatible<sup>†\*1</sup>
 Phonebook (50 Entries)<sup>\*1</sup>
 Ringer Indicator

 \*1 Except KX-TS520EX1 / EX2.





Ringer Indicator



KX-TS580EX1/EX2 Black

www.beophone.rs



Speakerphone

### A Simple, Easy-to-Use Design to Match Every Need



### KX-TS580EX1/EX2 KX-TS560EX1/EX2 KX-TS520EX1/EX2

#### Integrated Telephone System

The KX-TS580EX1/EX2 and KX-TS560EX1/EX2 Equipped with Handy Features, Including Both LCD Display and Caller ID

#### 🐚 NO CHEMICAL USED

RoHS-specified No Chemical Used substances Lead, cadmium, mercury, hexavalent chromium and specified brominated flame retardants (PBB and PBDE).

#### Outstanding Features with Built-In Quality

#### **Caller ID Compatible<sup>+</sup>**

The KX-TS580EX1 / EX2 and KX-TS560EX1 / EX2 are suitable for Caller ID service. The 2-Line LCD displays caller's name (required registration in phonebook) and number.

You can know who's calling before you answer. Except KX-TS520EX1 / EX2.

<sup>+</sup> Requires subscription to Caller ID service by a telephone company.

#### Phonebook (50 Entries)

456-789-\*0#-

Up to 50 numbers and names can be stored in its phonebook. You can make a call by selecting a name or number from the phonebook. Except KX-TS520EX1 / EX2.

KX-TS580EX1/EX2 Black

#### **Ringer Indicator**

You can confirm incoming calls visually. Ringer Indicator flashes to indicate there is an incoming call.

Convenient when waiting for a call.

Specifications	KX-TS580EX1	KX-TS580EX2	KX-TS560EX1	KX-TS560EX2	KX-TS520EX1	KX-TS520EX2
www.beophone.rs	Black		Black		Black Black Brd	
General						
Number of Line	1		1			1
Data Port	•		•		•	
One Touch Dial	-		_		3	
Redial Memory	20-Station		20-Station		Last One	
Auto Redial	•		—		—	
One Touch Redial	• (Last One)		• (Last One)		• (Last One)	
Phonebook Name Input	English (50 Entries)		English (50 Entries)		_	
Pulse / Tone Default	Tone Fix		Tone Fix		Tone Fix	
Flash Time	Programmable		Programmable		100 ms Fix	
Flash Time Default	100 ms		100 ms		_	
Insertable Pause	3.5 s		3.5 s		2.1 s	
Ringer Volume	Off / Low / High		Off / Low / High		Off / Low / High	
Ringer Indicator	•		•		٠	
Electronic Hold	•		—		-	
Electronic Hold on Music	•		_		_	
Speakerphone	•		—		-	
Speakerphone Volume	8-Step		—		-	
Mute	•		•		—	
On-Hook Dialing	•		•		—	
Handset Receiver Volume	4-Step		4-Step		6-Step	
Call Restriction	Programmable (0 or Up to 2 digits)		Programmable (0 or Up to 2 digits)		-	
Dial Lock	•		•		-	
Navigator	•		•		-	
LCD						
LCD	Dot x 16 digits 7-Seg x 8 digits + Pict		Dot x 16 digits 7-Seg x 8 digits + Pict		—	
LCD Language (Menu Selection)	English / Spanish / Italian / Greek / Turkish / German		English / Spanish / Italian / Greek / Turkish / German		-	
LCD Language Default	English		English		_	
LCD Contrast	4-5	Step	4-9	Step		_
Caller ID						
Caller ID Compatible	•		•		_	
Signal	FSK&DTMF		FSK&DTMF		-	
Private Name Display	<ul> <li>(Required Registration in Phonebook)</li> </ul>		<ul> <li>(Required Registration in Phonebook)</li> </ul>		—	
Caller ID Memory	50-Station		50-Station		—	
Time / Day Stamp from Clock	•		•		—	
Others						
Power Source	3 x AA and Line		3 x AA and Line		Line	
Wall Mountable	•		•		•	
Dimensions W x D x H (mm)	196 x 190 x 95		196 x 190 x 95		196 x 190 x 95	
Weight (g)	685		665		518	

